

UT136C

POCKET DMM, AUTO-RANGING



- 3 3/4 digits LCD, max. reading 3999
- Data hold for easy reading
- Continuity check with buzzer
- Enhanced protection, 10A fused
- Elegant design with integrated holster, ideal for DIY users & hobbyists
- Safety as per IEC1010-1 CAT.III 600V & CAT.IV 300V

Technical specifications

DCV: 400m/4/40/400/500V, $\pm 0.8\%$

ACV: 400m/4/40/400/500V, $\pm 1.2\%$

DCA: 400 μ /4m/40m/400m/4/10A, $\pm 1.0\%$

ACA: 400 μ /4m/40m/400m/4/10A, $\pm 1.2\%$

OHM: 400/4k/40k/400k/4M/40M Ω , $\pm 1.0\%$

TEMP: -40 $^{\circ}$ C~1000 $^{\circ}$ C, $\pm 2.5\%$

FREQ: 10Hz~10MHz, $\pm 0.5\%$

Duty cycle: 0.1%~99.9%

Audible continuity, diode test

Battery: 9Vx1, 6F22

Dimensions: 137x72x35mm

Weight: 200g approx. (incl. battery)

Accessories: temp probe

REF: 01U136C0000

CE (EMC), UL, CE (LVD)

Sinometer